



CWV-200 彩屏称重仪表

CWV-200 Color screen Weighing Indicator



CWV-200称重仪表采用五寸全彩触摸屏，支持最多8只传感器并联，实现高效、准确的称重数据读取。可视化操作标定与称重。配备网口、USB、RS485接口及64G储存卡，方便数据传输与存储。提供开关量输出及标准工业模拟量输出，满足多种应用需求。

The CWV-200 weighing indicator features a five-inch full-color touch screen and supports up to eight parallel in parallel to achieve efficient and accurate reading of weighing data. Visual operation calibration and weighing. Equipped with Ethernet, USB, and RS485 ports, along with a 64GB storage card for easy data transmission and storage. The device also provides switch output and standard industrial analog output to meet various application needs.

特点 Features

- 称重6位显示
- 称重温度漂移5位显示30字/8小时
- 全彩触摸可视化操作界面，可显示标定称重功能标
- 准最大64G TF存贮卡
- 5个独立开关量输出，2个独立开关量输入
- 模拟量输出功能（4~20mA, 0~10V）
- 具备100M通用网口、USB2.0及RS485接口
- 最多可并联接入8只模拟传感器，64只数字传感器
- 6-digit weight display
- 5-digit temperature drift display with 30 characters/8 hours
- Full-color touch visual operation interface, capable of displaying calibration and weighing functions
- Standard maximum 64G TF storage card
- 5 independent digital outputs, 2 independent digital inputs
- Analog output function (4-20mA, 0-10V)
- Equipped with 100M Ethernet port, USB 2.0 interface, and RS485 interface
- Up to 8 analog sensors and 64 digital sensors can be connected in parallel

技术参数 Specifications

精度	: 5/100,000	Accuracy	: 5/100,000
响应速度	: ≤200ms	Response Speed	: ≤200ms
电源	: 5V/600mA max	Power Voltage	: 5V/600mA max
RS485接口	: 独立RS485总线*2, 无线透传RS485总线*1	RS485 Interface	: Dual independent RS485 buses, one wireless transparent RS485 bus
无线485通讯距离	: ≥100M	Wireless 485 Communication Distanc	: ≥100M
触摸屏分辨率	: 800*480	Touch screen resolutio:n	: 800*480
仪表尺寸	: 126*103*30 mm	Instrument Dimensions	: 126*103*30 mm
选配1	: 可提供3.7~4.2V锂电池供电选配功能	Optional Features	: Can be powered by a 3.7~4.2V lithium battery
选配2	: 可提供悬挂支架	Optional Features	: hanging bracket
版本1	: 彩屏称重控制器	version 1	: Full-color screen weighing controller
版本2	: 彩屏称重仪表	version 2	: Full-color screen weighing indicator